



Technical Features MAX T220 HD

New DVB-T2 Standard (H.265)	DVB-T2 Free-to-Air Receiver	Weather information
Full HD up to 1080p	Parental Control	Teletext
1 HDMI (HDCP included)	1 scart	Screen photos
FTA Free channels	SPDIF: Coaxial digital audio output	Music player
Upgrade by USB	4000 channels	Video player
OSD multi-language	Electronic Program Guide (EPG)	Dolby Digital (Cristal clear sound)

Logistic and commercial information

Measures: 167x107x38 mm	Code: 0710039	Code EAN 13: 8436545306543
Gross weight 1 unit 0.52 Kg*	Packaging measures 1 unit: 190x165x50 mm	
Packaging: 10 pcs	Packaging measures 10 units: 400x270x185 mm	

*Pending verification



New DVB-T2 Standard (H.265)



Media Player



Full HD up to 1080i/p



HDMI (HDCP included)



DVB-T2 Free-to-Air Receiver



Parental Control



Electronic Program Guide



Dolby Digital



USB Update

DVB-T2 HD Receiver (H.265/HEVC Standard) MAX T220 HD

VIDEO	
Decoding Output Aspect ratio Active pixel (Scart) Active pixel (HDMI)	MPEG-4 H.264, MPEG-2, MP@ML, MPEG-4 H.265/AVC HP@L4 PAL / NTSC 4:3 PS, 4:3 LB, 16:9 480i / 576i 480i_60, 480p_60, 576i_50, 576p_50, 720p_50, 720p_60, 1080i_50, 1080i_60, 1080p_50, 1080p_60 HDMI / Scart
AUDIO	
Decoding Output connector	PCM / AAC / Dolby digital / Dolby Digital + HDMI / Scart / Coaxial SPDIF
DEMODULATOR	
Standard	DVB-T2 (EN 302-755 V 1.3.1) DVB-T (EN 300-744 V 1.61)
INPUT SIGNAL	
Frequency Input Level Bandwidth RF input connector Loop Through connector	47-862 MHz -77 dBm to -20 dBm 6, 7, 8 MHz IEC Female IEC Male
MISCELLANEOUS	
USB Connector Supply voltage External power supply Stand-by power consumption (Low Power Consumption mode) Power consumption Operation temperature Measures Net weight Network connection	USB 2.0 12Vdc-1A 100-240 Vac 50-60 Hz <1 W < 5 W 5°C to 40 °C 167 x 107 x 38 mm 0.38 Kg* 10/100 Mbits Ethernet

*Pending verification

