

# RG59

## RG-Cables acc. to MIL-C-17F, MIL-C-17G



### Application

see product overview

### Standards

According to MIL-C-17F, MIL-C-17G

### Flame resistance

acc. to IEC 60332-1

### Construction

Inner conductor	copperclad steel wire, diameter $0.59 \pm 0.01$ mm
Insulation	PE, diameter $3.70 \pm 0.05$ mm
Outer conductor	
Copper braid	bare, 95% optical coverage
Sheath	PVC, diameter $6.15 \pm 0.10$ mm

### Mechanical properties

Minimum bending radius	without load	5 x outer diameter
	with load	10 x outer diameter
Temperature	during operation	-40° C to + 85° C
	during installation	-15° C to + 55° C

### Electrical properties

at 20°C

Loop resistance		$\leq \square 165 \Omega/\text{km}$
Characteristic impedance		$75 \Omega \pm 3 \Omega$
Mutual capacitance		67 pF/m
Velocity ratio		66 %
Transfer impedance	3 MHz	36 mΩ/m
Operating voltage		1.7 kV <sub>rms</sub>
Test voltage	Inner/Outer conductor	7 kV <sub>rms</sub>

# RG59

## Electrical data

at 20°C

Frequency (MHz)	Attenuation (dB/100m)	Max. power rating (Watts) (ambient temperature 25°C and max. inner conductor temperature 70°C)	Return loss (dB) several peaks are allowed
	nominal	maximum	
10	3.5	1100	
100	11	340	
200	16	230	<b>Frequency (MHz)</b>
400	24	180	10-300 ≥ □26
1000	38	105	300-1000 ≥ □24

All other requirements acc. to MIL-C-17F, MIL-C-17G

## Technical data

Product code	Designation	Type	Brand name	Outer diameter	Weight	Standard delivery length	Drum size	Gross weight	Copper content	Tensile force
				mm	kg/km	m	*PWD/ring	kg		
1002721	2YCY	0.59/3.7 Staku	M17/29-RG59	6.15	53.6	1000/500 / 100	500/200/3 10 and 400/150/3 30	57/29/5 .5	24.7	145
1002726	2YCY	0.59/3.7 Staku	M17/29-RG59	6.15	53.6	1000/100 /500/	500/200/3 10 and 400/150/3 30	57/29/5 .5	24.7	145

\*PWD (Plywood drum)

## Product Code Table

Product Description	Product Code	PG Reference Code	PG Part Number
RG59 MIL-C-17F 100RW	1002721-00100RW	60026132	<b>60014299</b>
DR RG59 M17 75 0.59/3.7PVC BK 500DW	1002721-00500DW	60017535	<b>60017536</b>
DR RG59 M17 75 0.59/3.7PVC BK 1000DW	1002721-01000DW	60017535	<b>60017537</b>

© PRYSMIAN GROUP 2008, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.