


Technical datasheet for:

**SRV-M**



### General data

<b>Item</b>	Connector Box
<b>Description</b>	Sleeve to repair light damages of occupied and unoccupied ducts.
<b>Package unit</b>	10 Pcs.

### Technical data

Quality	Value		Unit
<b>Material</b>	PolyVinylChlorid - Unplastinized PVC-U		
<b>Dimension</b>	SRV-M 40:	d = 40; L = 455	mm
	SRV-M 50:	d = 50; L = 455	
<b>Pressure</b>	0,5		bar
<b>Tensile strength of the coating pipe of the SRV-G</b>	SRV-M 40:	550	N
	SRV-M 50:	700	
<b>Pressing operation clamp on case</b>	min. 1550		N

**gabocom is certified by the quality system following DIN EN ISO 9001, the environmental management system DIN EN ISO 14001 and the energy management system DIN EN 50001.**

**The used materials meet the REACH default (EU regulation 1907/2006) and the RoHS default (EU guidelines 2011/65).**

gabo Systemtechnik GmbH  
Am Schaidweg 7  
94559 Niederwinkling  
GERMANY

Tel. +49 9962 950-200  
Fax +49 9962 950-202  
info@gabocom.com  
www.gabocom.com

Editor: LF  
Release: MK  
Date: 03.12.2015  
Edition: 2

No responsibility is taken for the currency and completeness of details and information. This document can be revised and supplemented without prior notice. Liability for damages is excluded.